



[IPN Home](#) | [Search](#) | [Order](#) | [Shopping Cart](#) | [Login](#) | [Site Map](#) | [Help](#)



## JP9155185A: NOX ABSORBENT, MANUFACTURE THEREOF AND DEVICE USING NOX ABSORBENT

[View Images \(1 pages\)](#)

Country: JP Japan

Inventor(s): TATEISHI YASUSHI  
FURUNO SHUJI  
OKAZAKI MOTOHIRO

**BEST AVAILABLE COPY**

Applicant(s): TORAY IND INC



[News, Profiles, Stocks and More about this company](#)

Issued/Filed Dates: June 17, 1997 / Dec. 7, 1995

Application Number: JP1995000319017

IPC Class: [B01J 020/08](#); [B01D 053/02](#); [B01D 053/14](#); [B01D 053/56](#); [B01D 053/81](#);

**Abstract:** **Problem to be solved:** To obtain an NOx absorbent capable of efficiently absorbing/removing a low concentration of NOx contained in a combustion exhaust gas by adding the oxide of one type of element selected from among iron, nickel, manganese, copper, cobalt, chromium and zinc to a porous alumina as a main component.

**Solution:** A lowly concentrated NOx absorbent is formed of a porous alumina as a main component and the oxide of element selected from iron, nickel, manganese and cobalt borne by the porous alumina. In this case, the average pore diameter or/and the peak pore diameter of the porous alumina are 0.2-10nm and the pore volume is 0.03cc/g. Further, this lowly concentrated NOx absorbent is caused to release the once absorbed NOx by heating the absorbent at 300-600°C. Besides, the NOx absorbent is capable of maintaining the NOx removing rate at 80% or more in the air at a space velocity of 10.324h<sup>-1</sup> and a linear velocity of 39cm/s and under other atmospheric conditions such as NOx concentration of 3.0ppm, moisture concentration of 1.5% and temperature of 25°C. This NOx-removing rate should persist for 10 hours or more.

COPYRIGHT: (C)1997,JPO

Foreign References: none